

Liebherr A900 Low Rail (Type 9C)

WHEELED RRV EXCAVATOR

SPECIFICATION

Tailswing gauge exceedence 590mm Maximum underside height of tailswing 1283mm Max travel speed on rail 20km/h Towing Capacity 280t Max CANT working 150mm Max CANT travelling 200mm Max CANT on/off tracking 150mm Max Gradient 1 in 25	Overall weight	23t
Max travel speed on rail 20km/h Towing Capacity 280t Max CANT working 150mm Max CANT travelling 200mm Max CANT on/off tracking 150mm	Tailswing gauge exceedence	590mm
Towing Capacity 280t Max CANT working 150mm Max CANT travelling 200mm Max CANT on/off tracking 150mm	Maximum underside height of tailswing	1283mm
Max CANT working150mmMax CANT travelling200mmMax CANT on/off tracking150mm	Max travel speed on rail	20km/h
Max CANT travelling 200mm Max CANT on/off tracking 150mm	Towing Capacity	280t
Max CANT on/off tracking 150mm	Max CANT working	150mm
	Max CANT travelling	200mm
Max Gradient 1 in 25	Max CANT on/off tracking	150mm
	Max Gradient	1 in 25

- Multi purpose RRV suitable for use with all attachments
- Two person cabs
- Towing capacity of 280t/12 trailers