



On-Track Plant Engineering Conformance Certificate

In accordance with RIS-1530-PLT – Issue 7.2

Certificate no.: 71/1186/25

Report no.: TRUK/B 24/170, (Issue 1, 27/09/2024). This report is an integral part of this Certificate.

Name of Plant Assessment Body	TÜV Rheinland UK Limited 5 Mallard Way Pride Park Derby DE24 8GX United Kingdom	Organisation Code:	71 (a UKAS accredited certification body No. 8400)
--------------------------------------	---	---------------------------	---

Vehicle Class / Description	940/Colmar/T10000FS/9B
------------------------------------	------------------------

Vehicle Asset Manager	Story Plant Ltd
Issue Date	24-03-2025
Expiry Date (if any)	21-03-2032

Vehicle Number(s)	ZZ709 940826-9
--------------------------	----------------

First in Class:	No
Certificate No. of First in Class:	ZZ709 940860-8 on ECC 71/1183/25, against RIS-1530-PLT Issue 7.1.

Authorised by: **Official Stamp of TRUK, CAB Rail**

e.Sig: NDC/TUV/25/0352

Certifier / Signatory Name Neil Charles Senior Engineer



Reason for Issue and Scope of Work

Previous Certificate:

Certification of upgraded Colmar T10,000FS Excavator against RIS-1530-PLT Issue 7.2.

This Certificate:

Amendment to Maintenance Instruction Details only. No engineering change.

Manufacturer Serial No.: 8730

Fleet No.: 1258

Assessed for compliance with RIS-1530-PLT, Issue 7.2.

Deviations associated with this Certificate (if none state "NONE")
NONE.

Previous Certificate No.
(if none state "NONE"): 71/1180/25

Maintenance Instruction Details

Maintenance Instruction Title: Story Road Rail - Colmar Operation & Maintenance Addendum

Maintenance Instruction Number: COLMAR-0681

Issue No.: 3

Date: 09/2024

Limitations of Use (these words are mandatory where applicable)

1. The RRV shall only operate inside a possession.
2. When travelling, the RRV is within W6a gauge as defined in RIS-1530-PLT.
3. When working the RRV may be out of W6a gauge.
Minimum underside height of tail swing above rail is 1385mm.
Maximum tail swing gauge exceedance with counter-weight retracted is 390mm, (1080mm from the running edge of the rail).
Maximum tail swing gauge exceedance with counter-weight extended is 1230mm, (1920mm from the running edge of the rail).
A site survey shall be undertaken to assess potential damage to the infrastructure equipment prior to use.
4. The RRV shall NOT on/off track, travel or work on live conductor-rail lines.
5. The RRV shall NOT on/off track, travel or work under live OLE, unless the SpaceGuard RCI system is active, the Height Limit correctly set and the system functionality has been proven correct prior to vehicle use.
The use of the RRV under live OLE shall only be in accordance with the safe system of work for the possession, determined and approved by taking guidance from the requirements of GE/RT8000-HB16 Issue 4, and account taken of:
 - A maximum SpaceGuard default height of the boom above the rail of 3.500m.
 - A minimum OLE wire height of 4.165m.
 - The earth bonds on the RRV shall have been examined for security and presence, prior to use.
 - Attachments and their loads shall not exceed the height of the top of the boom.
6. The RRV shall NOT work under live OLE with the dipper extension (Rhino Horn) fitted.
7. Except for the cab, when the RRV is under live OLE, access is NOT permitted onto any surfaces higher than 1.4m above rail.
8. The RRV shall NOT on/off track if the adjacent line or lines are open to traffic.
9. The RRV shall only be permitted to work ALO with the SpaceGuard RCI system active, the Slew Limit and/or Virtual Wall correctly set and the system functionality has been proven correct prior to use.
ALO working shall only be in accordance with the safe system of work for the possession, taking account of the extra gauge exceedance caused by attachments.
10. For access/egress, the RRV shall only operate with the door to the cab adjacent to a cess or a line closed to all train movements, or a safe system of work takes account of adequate clearances to adjacent lines.
11. The RRV shall NOT travel on track with:
 - Cants greater than 200mm;
 - Gradients greater than 1:25 and/or;
 - Curves less than 80m.
12. The RRV shall NOT work on track with:
 - Cants greater than 180mm;
 - Gradients greater than 1:25 and/or;
 - Curves less than 80m.
13. When reversing, the RRV shall only proceed at walking speed with the driver utilising the CCTV and/or ground staff, until the superstructure/boom can be slewed to face the direction of travel.
14. For on/off tracking, a site specific work plan shall be used taking account of the requirements in Network Rail Infrastructure Plant Manual NR/L2/RMVP/0200.
The RRV shall NOT be on/off tracked on:
 - Cants greater than 150mm and/or;
 - Gradients greater than 1:25.
15. The RCI shall be switched on at all times, unless in digging mode.
16. The RCI has a tandem lifting mode.
17. The RRV is permitted to tow and/or propel rail trailers with both air service and park braking systems coupled.
Maximum braked towed/propelled weight is 80 tonnes (chassis towing point), 25 tonnes (axle towing point) 4 trailers shall not be exceeded at any towing point.
Air supply pressure for the service brake application is 0-8bar and park brake release is maximum 8bar.
NOTE: The maximum towed and/or propelled weight may have to be reduced where the railhead conditions for adhesion and/or running gradient may affect the safe traction performance of the RRV.

Supplementary Information - (Optional – minimum requirements where applicable)

1. The RRV is a OEM Colmar T10,000FS with 4.07m boom and 2.10m tele dipper.
2. Manufacturer Serial No. 8730, Story Contracting Fleet No. 1258.
3. The RRV is approved to carry 2 – persons seated in the driver's cab.
4. The RRV operates on rail in high-mode only.
5. 360 Degree CCTV camera fitted to the machine.
6. Gross vehicle weight is 32 tonnes.
7. Fitted with rail wheel braking system.
8. Fitted with Auxiliary Lifting Point, SWL 7.5 tonnes.
9. Maximum permitted speeds on rail not to exceed:

• 20mph Plain line (Travelling);	• 5mph towing/propelling;
• 5mph Plain line (Working)	• 5mph switches and crossings;
• 5mph emergency recovery.	• 5mph raised check/guard rails
10. Where an attachment is known to have a significant adverse effect on the RRV stability, the RCI shall always be in 'Lift Mode' when using the attachment.
11. Controlled by Screen 1 - RCI information for 0 to 150mm Cant configuration:
 - Model: GKD 3RCI Touch Screen;
 - Software: V9.61 BSP.
 - Duty chart references: Serial 8730, all charts, Date 20-Mar-2025.
12. Controlled by Screen 2 - RCI information for 0 to 180mm Cant configuration:
 - Model: GKD 3RCI Touch Screen;
 - Software: V9.61 BSP.
 - Duty chart references: Serial 8730, Date 20-Mar-2025.
13. The configuration change-over process, Items 11 and 12 above, shall be in accordance with Story manual STORY/MP/180MMCANT.

14. Fitted with GKD SpaceGuard RCI system that has been approved by Network Rail Technical Services. Document reference MLD/L044 details the: "Approval of MLD026 Colmar/GKD SpaceGuard T10,000FS, against RIS-1530-PLT Issue 5. The "Limitations of Use" on this certificate permit operation of this RRV with Adjacent Line Open (ALO) and/or under live Overhead Line Equipment (OLE).
15. The RRV has Normal and Tandem Lifting Modes.
16. Dipper Extension (Rhino Horn):
The RRV may be used with the dipper extension (Rhino Horn) in accordance with an approved method statement and a safe system of work.
SpaceGuard is deactivated when Rhino Horn is fitted.
The RRV shall NOT work under live OLE with the Rhino Horn fitted.
Functional test shall be undertaken prior to work on Network Rail Infrastructure